


BREAK SHARP CORNERS MAY BE EITHER CHAMFER OR RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.

THIS DRAWING IS A SOLE PROPERTY OF M & M I t d. IT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THEIR CONSENT

REFER PART NO. - H07650885U91

REF PART NO:

UNSPECIFIED TOLERANCES FOR PART		SURFACE FINISH SYMBOLS:ISO-1302		 MAHINDRA & MAHINDRA LTD. FARM DIVISION, INDIA					
FORMING TO FORMING	UPTO 500 ±0.5 ABOVE 500 ±0.8	WELDING SYMBOLS:IS813							
CD BETWEEN HOLES	IN ONE PLANE ±0.2 IN DIFF PLANES±0.5	REMOVE ALL SHARP CORNERS & BURRS							
FORM TO PIERCE	±0.5	DO NOT SCALE ALL DIMENSIONS ARE IN mm	<SC> COUNT : 0	NAME		DATE	PROJECT CODE:		
HOLE SIZES	+0.2/-0		<CC> COUNT▽ 0	DSNR	AR	04-08-2021	ER NUMBER: ER22I0000024		
SLOT SIZES	±0.8		WEIGHT(kg) :	CHKR	AR	04-08-2021	DESCRIPTION :		
FLANGE WIDTH	+1.0/-0.7		S/F AREA(cm²):	APPR	NVC	04-08-2021	FUEL TANK ASSY EXPORT		
JOGGLE DEPTH	+0.3/0		MATERIAL:				PART NUMBER :		CL:
UNSPECIFIED TOLERANCES FOR PART & ASSEMBLY			REFER BOM				0P7652201U91		NA
GENERAL TOLERANCES	UP TO 300 ±0.8 ABOVE 300 ±1.0				DWG.SIZE : A4		SCALE : 1:1		SHEET: 1 OF 1
ANGULAR TOLERANCE	±1°								